IN THE CLAIMS

Please substitute the attached Listing of Claims for all prior claims of record.

Listing of Claims

1. (Currently Amended) A milling roller comprising a roller base body (19) driven by a milling roller drive device (11 to 15) via a transmission unit (32), ~~and~~ a ~~one-pieced~~ one-piece tubular milling tube (25) ~~to be~~ coaxially slidably mounted from one side on the roller base body (19) ~~and to be attached~~ in a manner allowing exchange thereof, the milling tube (25) carrying cutting tools on ~~its~~ an outer surface (46), ~~characterized in that~~ the milling tube (25) ~~comprises~~ includes fastening elements (28)[[,]] radially projecting from ~~the~~ an inner surface (44) of the milling tube (25)[[,]] by which the milling tube (25) can be ~~mounted~~ secured in a rotationally fixed manner to at least one of the roller base body (19) ~~or to~~ and a member connected to the roller base body (19), and means for securing said fastening elements (28) to at least one of the roller base body (19) and a member connected to the roller base body (19).

B4

2. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the fastening elements (28) are arranged on at least one axial end ~~side~~ of the milling tube (25).

3. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the milling tube (25) is fastened to an axial end ~~side~~ of the roller base body (19) and is radially supported on ~~the other~~ another axial end ~~side~~.

4. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the inwardly fastening elements (28) ~~comprise~~ are flange members projecting radially ~~inward~~ inwardly from the milling tube (25).

B4

5. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the milling tube (25) is arranged at a radial distance from the roller base body.

6. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the milling tube (25) ~~axially~~ projects axially relative to the roller base body (19).

7. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the member connected to the roller base body (19) ~~comprises~~ includes the transmission unit (32) integrated into the roller base body (19).

8. (Currently Amended) The milling roller according to claim 1[[,[[~~characterized in that~~ wherein the milling tube (25) is radially supported at two axially spaced positions on the roller base body (19).

9. (Currently Amended) The milling roller according to claim 8[[,]] ~~characterized in that~~ wherein the support ~~comprises~~ includes radial guide elements (26; 33; 42) fastened ~~either~~ at least one of (a) radially outside on the roller base body (19), ~~or~~ (b) radially inside on the milling tube (25), ~~or are arranged~~ and (c) between the roller base body (19) and the milling tube (25).

10. (Currently Amended) The milling roller according to claim 8[[,]] ~~characterized in that~~ wherein the support ~~comprises~~ includes radial guide elements (42), ~~wherein~~ and the guide elements (42) are integrally connected to the ~~at least one~~ fastening ~~element~~ elements (28).

B4

11. (Currently Amended) The milling roller according to claim 9, characterized in that the support comprises radial guide elements (26), ~~wherein~~ and the guide elements (26) are arranged on ~~the~~ a free end side of the roller base body (19).

12. (Currently Amended) The milling roller according to claim 9[[,]] ~~characterized in that~~ wherein the radial guide elements ~~can comprise~~ include radially acting tensioning elements (60, 62, 64).

13. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~[[,]] wherein at least one support ring (33) is arranged as a radial guiding element between the milling tube (25) and the roller base body (19)[[,]] ~~at least one support ring (33) is arranged as a radial guiding element~~.

14. (Currently Amended) The milling roller according to claim 15[[,]] ~~characterized in that~~ wherein the at least one supporting ring (33) ~~comprises~~ includes at least two radially tensioned segment rings (60, 62, 64).

15. (Currently Amended) The milling roller according to claim 13[[,]] ~~characterized in that~~ wherein the at least one support ring (33) is arranged for axial displacement relative to the roller base body (19) and the milling tube (25).

16. (Currently Amended) The milling roller according to claim 14[[,]] ~~characterized in that~~ wherein the segment rings (62, 62, 64) are wedge-shaped in cross section.

B4

17. (Currently Amended) The milling roller according to claim 13[[,]] ~~characterized in that~~ wherein the at least one support ring (33) ~~comprises~~ includes a central ring (60) having a trapezoidal shape in cross section ~~and~~ arranged to be axially tensioned against a radially outer ring (62) and a radially inner ring (64) which ~~have~~ has an opposite trapezoidal shape in cross-section, and pressing the outer ring (62) presses against the milling tube (25) and the inner ring (64) presses against the roller base body (19).

18. (Currently Amended) The milling roller claim 13[[,]] ~~characterized in that~~ wherein the at least one support ring (33) is divided into at least two ~~or more~~ parts in the circumferential direction.

19. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the transmission unit (32) is arranged at ~~the~~ an end of the roller base body (19) facing toward the milling roller drive device (11 to 15).

20. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the transmission unit (32) is arranged at ~~the~~ an end of the roller base body (19) facing away from the milling roller drive device (11 to 15), and the transmission unit (32) ~~being~~ is connected to the milling roller drive device (11 to 15) by a shaft (56) guided through the roller base body (19).

21. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the roller base body (19) is supported in two side walls (16, 17) of a roller box (31), ~~the~~ one side wall (17) facing away from the milling roller drive device (11 to 15) can be displaced by one of a pivoting and axis-parallel movement, and the ~~pivotable~~ one side wall (17) in the closed condition receives ~~the~~ a movable bearing (24) of the roller base body (19).

B4

22. (Currently Amended) The milling roller according to claim 21[[,]] ~~characterized in that~~ wherein the movable bearing (24) ~~comprises~~ includes an outwardly tapering guide member (40) and ~~that the~~ a side wall (17) thereof ~~comprises~~ includes a correspondingly tapering recess (41) receiving the guide member (40).

23. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the roller base body (19) is supported in two side walls (16, 17) of a roller box (31), and a machine cover (21) arranged on the milling roller drive device (11 to 15) is provided with openings (23) allowing access to fastening elements (20) between the side wall (16) facing toward the milling roller drive device (11 to 15) and the transmission unit (32) without a demounting of machine parts.

24. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that the~~ wherein a free end of the milling tube (25) is provided with a protective sleeve (39) for the inner surface (44).

25. (Currently Amended) The milling roller according to claim 13[[,]] ~~characterized in that the~~ wherein a protective sleeve (39) projects from the supporting ring (33).

B4

26. (Currently Amended) The milling roller according to claim 1[[,]] ~~characterized in that~~ wherein the roller base body (19) is surrounded by a protective tube (38).

27. (Currently Amended) The milling roller according to claim 13[[,]] ~~characterized in that~~ wherein the protective tube (38) ~~comprises~~ includes recesses (37) arranged in a uniform distribution at predetermined axial distances on the circumference[[,]] for receiving the support ring (33).

28. (Cancelled).

29. (Currently Amended) The milling roller according to claim 11[[,]] ~~characterized in that~~ wherein the radial guide elements ~~can comprise~~ include radially acting tensioning elements (60, 62, 64).

30. (Currently Amended) The milling roller according to claim 14[[,]] ~~characterized in that~~ wherein the at least one support ring (33) is arranged for axial displacement relative to the roller base body (19) and the milling tube (25).

31. (Currently Amended) The milling roller according to claim 15[[,]] ~~characterized in that~~ wherein the segment rings (62, 62, 64) are wedge-shaped in cross section.

B4

32. (Currently Amended) The milling roller according to claim 24[[,]] ~~characterized in that~~ wherein the protective sleeve (39) projects from the supporting ring (33).

33. (Currently Amended) The milling roller according to claim 26[[,]] ~~characterized in that~~ wherein the protective tube (38) ~~comprises~~ includes recesses (37) arranged in a uniform distribution at predetermined axial distances on the circumference[[,]] for receiving the support ring (33).